

EVde-ROT 4 Series

Copper free Aluminium signaling fixtures with rotating light, painted RAL 6003, with 2 off M25 entries as standard. Evde-ROT-4 is available in the following colours: blue / orange / red / green / yellow / transparent.

Specifications

Material	Copper-free aluminium (Cu <0.1%)
Temperature	-50°C to 60°C
IP Rating	IP65-66
Approvals	INERIS 01ATEX0019X GOST Certificate
- Atex	
- GOST	
Standards	EN/IEC: 60079-0, 60079-1, 60079-7 EN: 61241-0, 61241-1
Ex-code	Ⓔ II 2 GD Ex d IIC T5 / T4 Ex tD A21 IP65 T100°C / T135°C Ex de IIC T5 / T4 Ex tD A21 IP65 T100°C / T135°C
	According to European Directive 94/9/EC (ATEX) For Zone 1 & 2 and Zone 21 & 22
Gaskets	O-ring made in Nitrile Rubber (NBR)
Surface treatment	External polyurethane painting (RAL 6003)
Entries	Nr. 2 M25 entries
Hardware and Screw	Stainless steel external hardware
Lamps	Lamp included
Lamps Wattage	25W
Ballast	N.A.
Rated operation voltage (UE)	12Vac / 24Vac / 48Vac / 110Vac / 230Vac / 240Vac 12Vdc / 24Vdc / 48Vdc
Frequency	50/60 Hz
Accessories	Customized colours
Note	Continuous Running



Signalling lighting fixtures with rotating light

Type	Colour	Voltage	Dimensions	Weight kg	Power (W)
EVde-ROT-4	Transparent	12V cc	220x516	8.500	45
EVde-ROT-4	Transparent	24V cc	220x516	8.500	45
EVde-ROT-4	Transparent	48V cc	220x516	8.500	45
EVde-ROT-4	Transparent	12V ac 50-60Hz	220x516	8.500	25
EVde-ROT-4	Transparent	24V ac 50-60Hz	220x516	8.500	25
EVde-ROT-4	Transparent	48V ac 50-60Hz	220x516	8.500	25
EVde-ROT-4	Transparent	110V ac 50-60Hz	220x516	8.500	25
EVde-ROT-4	Transparent	230V ac 50-60Hz	220x516	8.500	25
EVde-ROT-4	Transparent	240V ac 50-60Hz	220x516	8.500	25



STL International Ltd
Hill Farm, Linton Hill
Linton, Maidstone
Kent, ME17 4AL
United Kingdom
tel. +44 (0)1622 749633
fax. +44 (0)1622 746800
email. solutions@stl-int.co.uk
web. www.stl-int.co.uk



Type	Colour	Voltage	Dimensions	Weight kg	Power (W)
EVde-ROT-4	Blue	12V cc	220x516	8.500	45
EVde-ROT-4	Blue	24V cc	220x516	8.500	45
EVde-ROT-4	Blue	48V cc	220x516	8.500	45
EVde-ROT-4	Blue	12V ac 50-60Hz	220x516	8.500	25
EVde-ROT-4	Blue	24V ac 50-60Hz	220x516	8.500	25
EVde-ROT-4	Blue	48V ac 50-60Hz	220x516	8.500	25
EVde-ROT-4	Blue	110V ac 50-60Hz	220x516	8.500	25
EVde-ROT-4	Blue	230V ac 50-60Hz	220x516	8.500	25
EVde-ROT-4	Blue	240V ac 50-60Hz	220x516	8.500	25

Type	Colour	Voltage	Dimensions	Weight kg	Power (W)
EVde-ROT-4	Orange	12V cc	220x516	8.500	45
EVde-ROT-4	Orange	24V cc	220x516	8.500	45
EVde-ROT-4	Orange	48V cc	220x516	8.500	45
EVde-ROT-4	Orange	12V ac 50-60Hz	220x516	8.500	25
EVde-ROT-4	Orange	24V ac 50-60Hz	220x516	8.500	25
EVde-ROT-4	Orange	48V ac 50-60Hz	220x516	8.500	25
EVde-ROT-4	Orange	110V ac 50-60Hz	220x516	8.500	25
EVde-ROT-4	Orange	230V ac 50-60Hz	220x516	8.500	25
EVde-ROT-4	Orange	240V ac 50-60Hz	220x516	8.500	25

Type	Colour	Voltage	Dimensions	Weight kg	Power (W)
EVde-ROT-4	Red	12V cc	220x516	8.500	45
EVde-ROT-4	Red	24V cc	220x516	8.500	45
EVde-ROT-4	Red	48V cc	220x516	8.500	45
EVde-ROT-4	Red	12V ac 50-60Hz	220x516	8.500	25
EVde-ROT-4	Red	24V ac 50-60Hz	220x516	8.500	25
EVde-ROT-4	Red	48V ac 50-60Hz	220x516	8.500	25
EVde-ROT-4	Red	110V ac 50-60Hz	220x516	8.500	25
EVde-ROT-4	Red	230V ac 50-60Hz	220x516	8.500	25
EVde-ROT-4	Red	240V ac 50-60Hz	220x516	8.500	25

Type	Colour	Voltage	Dimensions	Weight kg	Power (W)
EVde-ROT-4	Green	12V cc	220x516	8.500	45
EVde-ROT-4	Green	24V cc	220x516	8.500	45
EVde-ROT-4	Green	48V cc	220x516	8.500	45
EVde-ROT-4	Green	12V ac 50-60Hz	220x516	8.500	25
EVde-ROT-4	Green	24V ac 50-60Hz	220x516	8.500	25
EVde-ROT-4	Green	48V ac 50-60Hz	220x516	8.500	25
EVde-ROT-4	Green	110V ac 50-60Hz	220x516	8.500	25
EVde-ROT-4	Green	230V ac 50-60Hz	220x516	8.500	25
EVde-ROT-4	Green	240V ac 50-60Hz	220x516	8.500	25

Type	Colour	Voltage	Dimensions	Weight kg	Power (W)
EVde-ROT-4	Yellow	12V cc	220x516	8.500	45
EVde-ROT-4	Yellow	24V cc	220x516	8.500	45
EVde-ROT-4	Yellow	48V cc	220x516	8.500	45
EVde-ROT-4	Yellow	12V ac 50-60Hz	220x516	8.500	25
EVde-ROT-4	Yellow	24V ac 50-60Hz	220x516	8.500	25
EVde-ROT-4	Yellow	48V ac 50-60Hz	220x516	8.500	25
EVde-ROT-4	Yellow	110V ac 50-60Hz	220x516	8.500	25
EVde-ROT-4	Yellow	230V ac 50-60Hz	220x516	8.500	25
EVde-ROT-4	Yellow	240V ac 50-60Hz	220x516	8.500	25