

EVde-XN / EVde-MXN / EVcc-MXN Series

Signaling luminaire with flashing light and Fresnel lens manufactured in a Copper free Aluminium body, painted RAL 6003 with 2 off M25 entries as standard. EVde-XN is available in different colours and voltages.

Specifications

Material	Copper-free aluminium (Cu<0.1%)
Temperature	-50°C to 60°C
IP Rating	IP65-66
Approvals	INERIS 01ATEX0019X
- Atex	GOST Certificate
- GOST	
Standards	EN/IEC: 60079-0, 60079-1, 60079-7
	EN: 61241-0, 61241-1
Ex-code	<p>⊕ II 2 GD</p> <p>Ex d IIC T5 / T4</p> <p>Ex tD A21 IP65 T100°C / T135°C</p> <p>Ex de IIC T5 / T4</p> <p>Ex tD A21 IP65 T100°C / T135°C</p>
Gaskets	According to European Directive 94/9/EC (ATEX)
Surface treatment	For Zone 1 / Zone 2, Zone 21 / Zone 22
Entries	O-ring made in Nitrile Rubber (NBR)
Hardware and Screw	External polyurethane painting (RAL 6003)
Lamps	Nr. 2 M25 entries
Lamps Wattage	Stainless steel external hardware
Rated operation voltage (UE)	Lamp included
	10W, 25W, 50W
Frequency	110Vac / 230Vac / 240Vac
	12Vdc / 24Vdc
Note	50/60 Hz
	Continuous Running



Evde-...XN Signalling lighting fixtures with flashing light

Type	Power W	Dimensions	Weight kg
EVde-XN-3 12/24V cc	10	195x450	5.100
EVde-XN-3 110V ca	10	195x450	5.100
EVde-XN-3 230-240V ca	10	195x450	5.100
EVde-MXN-3 12/24V cc	25	195x450	5.100
EVde-MXN-3 110V ca	25	195x450	5.100
EVde-MXN-3 230-240V ca	25	195x450	5.100
EVcc-MXN-5 12/24V cc	50	195x450	5.100
EVcc-MXN-5 110V ca	50	195x450	5.100
EVcc-MXN-5 230-240V ca	50	195x450	5.100

Note. This is a Sintesis table, which means that in each line you can choose among different combination of colors and voltage



Listed below you can find all the possible combinations, each of them listed with a unique code...

Type	COLOR	VOLTAGE	Power (W)	Dimensions	Weight kg
EVde-XN-3	Blue	12V cc	10	195x450	5.100
EVde-XN-3	Blue	24V cc	10	195x450	5.100
EVde-XN-3	Blue	110V ac	10	195x450	5.100
EVde-XN-3	Blue	230-240V ac	10	195x450	5.100
EVde-MXN-3	Blue	12V cc	25	195x450	5.100
EVde-MXN-3	Blue	24V cc	25	195x450	5.100
EVde-MXN-3	Blue	110V ac	25	195x450	5.100
EVde-MXN-3	Blue	230-240V ac	25	195x450	5.100
EVcc-MXN-5	Blue	12V cc	50	195x450	5.100
EVcc-MXN-5	Blue	24V cc	50	195x450	5.100
EVcc-MXN-5	Blue	110V ac	50	195x450	5.100
EVcc-MXN-5	Blue	230-240V ac	50	195x450	5.100

Type	COLOR	VOLTAGE	Power (W)	Dimensions	Weight kg
EVde-XN-3	Orange	12V cc	10	195x450	5.100
EVde-XN-3	Orange	24V cc	10	195x450	5.100
EVde-XN-3	Orange	110V ac	10	195x450	5.100
EVde-XN-3	Orange	230-240V ac	10	195x450	5.100
EVde-MXN-3	Orange	12V cc	25	195x450	5.100
EVde-MXN-3	Orange	24V cc	25	195x450	5.100
EVde-MXN-3	Orange	110V ac	25	195x450	5.100
EVde-MXN-3	Orange	230-240V ac	25	195x450	5.100
EVcc-MXN-5	Orange	12V cc	50	195x450	5.100
EVcc-MXN-5	Orange	24V cc	50	195x450	5.100
EVcc-MXN-5	Orange	110V ac	50	195x450	5.100
EVcc-MXN-5	Orange	230-240V ac	50	195x450	5.100



STL International Ltd
 Hill Farm, Linton Hill
 Linton, Maidstone
 Kent, ME17 4AL
 United Kingdom
 tel. +44 (0)1622 749633
 fax. +44 (0)1622 746800
 email. solutions@stl-int.co.uk
 web. www.stl-int.co.uk